



## Silverline 300/400/500/600

- 300, 400, 500 or 600 gallon stainless steel tank includes full length mechanical agitation
- Galvanized frame
- Fan options:
  - 32" 12 blade polyamide variable pitch fan, stainless steel blower housing, 2 speed gearbox with neutral
  - 36" 16 blade polyamide variable pitch fan, stainless steel blower housing, 2 speed gearbox with neutral
  - 36" Super 8 blade polyamide variable pitch fan, stainless steel fan housing and straightening vanes, heavy fiberglass discharge vanes, single speed gearbox
- Pump options:
  - Myers 2-stage centrifugal pump, 70 gpm (265L) @ operation pressure 160 psi (11 bar)
  - Bertolini PAS908 pump, 3 piston diaphragm, 24 gpm (91L) @ 540 rpm pressure to 650 psi (45 bar)
  - Bertolini PAS144 pump, 3 piston diaphragm, 38 gpm (144L) @ 540 rpm pressure to 650 psi (45 bar)
- All non-corrosive plumbing
- Nozzle options:
  - 32" fan-7 single rollover ceramic nozzles per side with individual on/off valve and check valve on each nozzle
  - 36" 16 blade fan and 8 Blade super fan – 10 double rollover ceramic nozzles per side with individual on/off valve and check valve on each nozzle
- Walterscheid CV PTO shaft
- 4-way adjustable height settings with adjustable width axle

**\*\*Specifications subject to change without notification**

Durand-Wayland, Inc.  
P.O. Box 1404  
LaGrange, GA 30241  
Tel: 800.241.2308  
Fax: 706.884.3268

Durand-Wayland Machinery  
43016 Road 68  
Reedley, CA 93654  
Tel: 559.551.6904  
Fax: 559.551.4103

[www.Durand-Wayland.com](http://www.Durand-Wayland.com)