

## **COLLARD POLYVALENT EQUIPMENT LZP :** **MULTI FUNCTION FRAME FOR USE WITH LEAF REMOVER AND TRIMMER OPTIONS.**

### **A) POLYVALENT REINFORCED FRAME : Ref. 0073 1100**

- ◆ For a **front mounting exclusively**.
- ◆ **Oscillatory frame** with hydraulic parallelogram which allows to keep the top cutting element parallel to the ground or in a given position when moving the Trimmer.
- ◆ The oscillatory frame with hydraulic parallelogram allows to place the Trimmer well in line with the tractor which reduces the bulk on the road.
- ◆ Equipped with a **fast fixing**.
- ◆ Multi function : This frame allows to receive Trimmer, Leaf Remove, Bud Remove ...
- ◆ **Electric controls distributor** 1 simple effect + 5 double effect.
- ◆ Equipped with **3 cylinders** (with anti-fall safety valve):
  - . UP/DOWN : 1 x 800mm stroke ascending cylinder.
  - . 2 parallelogram cylinders with double rods (that means 2 double effect free for use).
- ◆ **Hydraulic block** (oil filter, oil flow limiter, drainage collector, motor valve).
- ◆ **Storage support**.
- ◆ With JIC connections.

### **B) TRIMMER PROFILMATIC® ELEMENT : Ref. P3000LZP**



- ◆ This machine is a vine Trimmer that operates **1 complete row** at the time, equipped with high speed rotation cutting system.
- ◆ Equipped with a **special cross-bar for the fast fixing**.
- ◆ Equipped with **3 hydraulic motors**.
- ◆ **anti-shock system = safety**.
- ◆ Equipped with **1 cross slope cylinder 90mm** (with an anti-fall safety valve) :
- ◆ **Cutting height = 1,70m** (4x480mm).
- ◆ 2 blades 480mm on the top cutting element = **0,78m**.
- ◆ Lateral and horizontal plastic protections.
- ◆ With a **storage support**.
- ◆ With JIC connections.

#### **OPTIONS FOR THE TRIMMER :**

REF. 0000 1833

- ◆ Manual height adjustment of the top cutting element

REF. 0000 2229

- Hydraulic height adjustment of the top cutting element

### **C) LEAF REMOVER ELEMENT : Ref. E3000 LZP**



- ◆ This machine is a Leaf Remover that operates **1 complete row** at the time.
- ◆ Equipped with a **special cross-bar for the fast fixing**.
- ◆ **Anti-shock system** on the 2 defoliating heads = **safety**.
- ◆ Equipped with **2 defoliating heads 180° double slots** with 2 different diameters (= Patented COLLARD).
- ◆ Equipped with **2 cylinders** for width adjustment (but only with 1 hydraulic function).
- ◆ **Slope adjustment by damper**.
- ◆ **Hydraulic height** adjustment **for one defoliating head** and **manual for the second head**.
- ◆ **Compleat air compressor** on the 3 points linkage.
- ◆ **3 ways pneumatic valve selector**.
- ◆ With a **storage support**.
- ◆ JIC connections.

